The include matcher accepts a variable number of arguments so that you can specify multiple substrings, array items, hash keys or key-value pairs:

11-matchers-included-in-rspec-expectations/02/higher_order_matchers.rb
```
expect('a string').to include('str', 'ing')
expect([1, 2, 3]).to include(3, 2)
expect(hash).to include(:name, :age)
expect(hash).to include(name: 'Harry Potter', age: 17)
```

This works well, but there is a gotcha related to variable numbers of items. Consider this example:

11-matchers-included-in-rspec-expectations/02/higher_order_matchers.rb
```
expecteds = [3, 2]
expect([1, 2, 3]).to include(expecteds)
```

This expectation fails, even though the array clearly includes 3 and 2. Here's the failure message:

```
expected [1, 2, 3] to include [3, 2]
```

The error message gives us a clue. This matcher expects the array to include([3, 2]), rather than to include(3, 2). It would pass if the actual array was something like [1, [3, 2]].

In order for RSpec to look for the individual items, you need to extract them from the array. You can do so by prefixing the expecteds argument with the Ruby splat operator:[5]

11-matchers-included-in-rspec-expectations/02/higher_order_matchers.rb
```
expect([1, 2, 3]).to include(*expecteds)
```

The include matcher is also available as a_collection_including, a_string_including, and a_hash_including, for when you're passing it into other matchers. As a higher-order matcher, include can also receive matchers as arguments—see *Operator Comparisons*, on page 191 or *Satisfaction*, on page 196 for examples.

start_with and end_with

These two matchers are useful when you care about the contents of a string or collection at the start or end but don't care about the rest. They work exactly the way their names imply:

11-matchers-included-in-rspec-expectations/02/higher_order_matchers.rb
```
expect('a string').to start_with('a str').and end_with('ng')
expect([1, 2, 3]).to start_with(1).and end_with(3)
```

5. http://ruby-doc.org/core-2.4.1/doc/syntax/calling_methods_rdoc.html#label-Array+to+Arguments+Conversion