All these matchers built into RSpec are designed to help you do two things:

- Express exactly how you want the code to behave, without being too strict or too lax
- Get precise feedback when something breaks so that you can find exactly where the failure happened

It's much more important to keep these two principles in mind than it is to memorize all the different matchers. As you try your hand at the following exercises, refer to Appendix 3, *Matcher Cheat Sheet*, on page 307 to get inspiration for different matchers to try.

Exercises

Since matchers help you diagnose failures, we want to show you how to get helpful failure messages by choosing the right matcher. *We wrote the following exercises to fail on purpose.* While you're certainly welcome to fix the underlying issue in as many exercises as you like, please focus first on experimenting with different matchers.

Matching Phone Numbers

Create a new spec file with the following description for a class that matches phone numbers from a string and yields them to its caller, one by one:

11-matchers-included-in-rspec-expectations/exercises/phone_number_extractor_spec.rb

```
RSpec.describe PhoneNumberExtractor do
  let(:text) do
    <<-EOS
      Melinda: (202) 555-0168
      Bob: 202-555-0199
      Sabina: (202) 555-0176
    EOS
  end

  it 'yields phone numbers as it finds them' do
    yielded_numbers = []
    PhoneNumberExtractor.extract_from(text) do |number|
      yielded_numbers << number
    end

    expect(yielded_numbers).to eq [
      '(202) 555-0168',
      '202-555-0199',
      '(202) 555-0175'
    ]
  end
end
```