## Your First Spec

Rather than testing some intricate production system, let's imagine something a little more concrete: a sandwich. Yes, it's silly, but it'll keep the examples short—plus, we were hungry while writing this chapter.

What's the most important property of a sandwich? The bread? The condiments? No, the most important thing about a sandwich is that it should taste good. Let's say so using the language of RSpec.

RSpec uses the words describe and it to express concepts in a conversational format:

- "Describe an ideal sandwich"
- "First, it is delicious"

Create a new project directory, with a subdirectory called spec. Inside «your_project»/spec, create a file called sandwich_spec.rb with the following contents:

01-getting-started/01/spec/sandwich_spec.rb

```
RSpec.describe 'An ideal sandwich' do
  it 'is delicious' do
  end
end
```

Developers work this way with RSpec all the time; they start with an outline and fill it in as they go. Add the following highlighted lines to your outline:

01-getting-started/02/spec/sandwich_spec.rb

```
RSpec.describe 'An ideal sandwich' do
  it 'is delicious' do
    sandwich = Sandwich.new('delicious', [])

    taste = sandwich.taste

    expect(taste).to eq('delicious')
  end
end
```

Before you run this spec, let's break the code down a bit.

### Groups, Examples, and Expectations

This file defines your tests, known in RSpec as your *specs*, short for *specifications* (because they *specify* the desired behavior of your code). The outer RSpec.describe block creates an *example group*. An example group defines what you're testing—in this case, a sandwich—and keeps related specs together.