We won't give an exhaustive reference here, but we would like to show you a few situations you're likely to run into. For a full list of everything you can specify for your arguments, see the docs.[4]

Argument Placeholders

When a method takes several arguments, you may care more about some than others. For instance, you may be stubbing a shopping cart's add_product method that takes a name, a numeric ID, and a vendor-specific code. If you only care about the name, you can pass the anything placeholder for the others:

14-customizing-test-doubles/02/setting_constraints.rb
```
expect(cart).to receive(:add_product).with('Hoodie', anything, anything)
```

You can also represent a sequence of anything placeholders with any_args:

14-customizing-test-doubles/02/setting_constraints.rb
```
expect(cart).to receive(:add_product).with('Hoodie', any_args)
```

The any_args placeholder is a bit like the "splat" operator that you use to define a Ruby method with a flexible number of arguments. It can go anywhere in the argument list, but it can only show up once. Any of the following calls would satisfy this particular constraint:

14-customizing-test-doubles/02/setting_constraints.rb
```
cart.add_product('Hoodie')
cart.add_product('Hoodie', 27182818)
cart.add_product('Hoodie', 27182818, 'HOODIE-SERIAL-123')
```

The counterpart to any_args is no_args:

14-customizing-test-doubles/02/setting_constraints.rb
```
expect(database).to receive(:delete_all_the_things).with(no_args)
```

As you might guess from the name, this constraint only matches when you call the method with no arguments.

Hashes and Keyword Arguments

A lot of Ruby APIs, especially ones written before Ruby 2.0 came out, use an options hash to provide a flexible interface for callers:

14-customizing-test-doubles/02/setting_constraints.rb
```
class BoxOffice
  def find_showtime(options)
    # ...
  end
end
```

4. https://relishapp.com/rspec/rspec-mocks/v/3-6/docs/setting-constraints/matching-arguments