You can then pass your custom matcher to any with constraint:

14-customizing-test-doubles/02/setting_constraints.rb
```
expect(box_office).to receive(:find_showtime).with(a_city_in_oregon)
```

RSpec Compares Arguments Using ===



You can constrain arguments using an ordinary Ruby value, a regular expression, one of RSpec's provided constraints, or any built-in or custom matcher. Behind the scenes, rspec-mocks compares method arguments using the === operator. Anything that supports === can be used as an argument constraint.

Custom argument constraints can reduce repetition and make your expectations easier to understand.

Constraining How Many Times a Method Gets Called

In addition to constraining a method's arguments, you can also specify how many times it should be called. For instance, some applications use a *circuit breaker* that stops trying network calls after a certain number of failures.[5] Here's how you might test a stock ticker class that protects its network client with a circuit breaker:

14-customizing-test-doubles/02/stock_ticker.rb
```
client = instance_double('NasdaqClient')
expect(client).to receive(:current_price).thrice.and_raise(Timeout::Error)
stock_ticker = StockTicker.new(client)
100.times { stock_ticker.price('AAPL') }
```

Even though we're calling stock_ticker.price many times, we expect the circuit breaker to stop hitting the network after the third simulated timeout error.

As you might guess from the name thrice, RSpec also provides once and twice modifiers. Since the English language doesn't provide any multiplicative adverbs after 3, you'll need to switch to the more verbose exactly(n).times constraint for other numbers:

14-customizing-test-doubles/02/stock_ticker.rb
```
expect(client).to receive(:current_price).exactly(4).times
```

When you don't care about the exact number of calls but have a certain minimum or maximum in mind, you can use at_least or at_most:

14-customizing-test-doubles/02/stock_ticker.rb
```
expect(client).to receive(:current_price).at_least(3).times
expect(client).to receive(:current_price).at_most(10).times
```

5. https://martinfowler.com/bliki/CircuitBreaker.html