Then, run bundle install to install rspec-rails. Finally, you can set your project up to use rspec-rails with the following command:

```
$ rails generate rspec:install
      create  .rspec
      create  spec
      create  spec/spec_helper.rb
      create  spec/rails_helper.rb
```

The .rspec file configures command-line arguments to pass into RSpec implicitly, just like we previously discussed in *Setting Command-Line Defaults*, on page 149. The one generated by rspec-rails will load spec_helper.rb for you on every RSpec run. The spec_helper.rb file, in turn, sets a number of helpful RSpec defaults—such as the verify_partial_doubles option we recommended in *Using Partial Doubles Effectively*, on page 271. It also provides some configuration suggestions in a commented-out section.

This installation process also creates a second configuration file, rails_helper.rb, but does *not* configure RSpec to require it by default. This file loads both Rails and rspec-rails, which sets up test features like model fixtures and database transactions.

These additional test features are useful or even essential for many specs—but not for all of them. In particular, we strive to build domain objects that have clear boundaries and don't depend directly on Rails. When we test these objects, we want the fastest feedback possible. Accordingly, we don't require rails_helper from a spec file unless it actually needs Rails.

Using rspec-rails

Once rspec-rails is installed, you'll be able to run your spec suite using either bundle exec rspec or bin/rake spec. Commands in the bin directory, like rake or rails, are Rails-generated binstubs (wrapper scripts) that save you the hassle of remembering to type bundle exec before every command.[2]

If you're used to creating binstubs via Bundler's --binstubs option as described in *Bundler*, on page 293, be aware that this option may not play nicely with Spring, a Rails preloader designed to speed up boot times.[3] You may see Rails commands hang or print warning messages from the Bundler-generated binstubs. To solve the problem, you'll need to either remove Spring or switch to the binstubs provided by Rails:

2. https://github.com/rbenv/rbenv/wiki/Understanding-binstubs
3. https://github.com/rails/spring