dynamic predicate matchers, 195
example groups, 111, 159
examples, 111, 159
failure messages, 177
higher-order matchers, 198–199, 201–202
identity and equality matchers, 189–190
it, 110
matchers, 177, 218
satisfaction matchers, 196
truthiness matchers, 191
:all hook scope, 117
all matcher, 197, 199, 202, 309
allow
configuring responses, 251–255, 261
constraining arguments, 256
vs. expect, 268
partial doubles, 241, 253
test doubles, 68, 241, 253
allow_any_instance_of, 276
an_instance_of matcher, 308
an_object_eq_to matcher, 190, 307
an_object_eql_to matcher, 190, 307
an_object_equal_to matcher, 190, 307
an_object_existing matcher, 310
an_object_having_attributes matcher, 202, 310
an_object_matching matcher, 201, 309
an_object_responding_to matcher, 310
an_object_satisfying matcher, 196, 310
and_call_original, 251–253, 255
and_raise, 251, 253
and_return, 251–252
and_throw, 251
and_wrap_original, 251, 254
and_yield, 251–252
and operator
custom matchers, 224, 226
matchers, 176, 178, 224, 226
any_args placeholder, 257
anything placeholder, 257
APIs, layers and driving public API, 62
arguments
constraining, 256–259, 261
hashes and keyword arguments, 257
injection, 279
placeholders, 257
resources on matchers, 257
tweaking for test doubles, 254
yielding, 314
around hooks
about, 113–114
configuring, 157
database transactions, 92, 140
Expense Tracker app examples, 118, 140
scope, 117
Arrange/Act/Assert pattern, 6, 73, 239, 271
arrays
embedding matchers, 176, 178
empty, 199
higher-order matchers, 197–202
nesting, 200
splat operator, 198–199
as_null_object, 239
as_of, 222, 226
as_stubbed_const, 278
assertions, *see* expectations
assign, 303
at_least modifier, 206, 259, 314
at_most modifier, 206, 259, 314
Atom RSpec Runner, 22
attribute matchers, 202, 310

B

-b option, 64, 148–149
background jobs, 303
--backtrace option, 64, 148–149, 160
backtraces
excluding frames, 160
filtering gems, 63
full, 64, 149, 160
output options, 148, 160
"banner year" matcher exercise, 211
bash, 99
basic_authorize, 123
BDD, *see* behavior-driven development (BDD)
be false matcher, 308
be matcher, 189, 307–308
be true matcher, 308
be_ prefix for dynamic predicate matchers, 194, 310
be_a matcher, 308
be_a_ prefix for dynamic predicate matchers, 194, 310
be_a_kind_of matcher, 308
be_an_ prefix for dynamic predicate matchers, 194, 310
be_an_instance_of matcher, 308
be_between matcher, 193, 290, 309
be_empty matcher, 9, 200
be_even matcher, 199
be_falsey matcher, 191, 308
be_falsy matcher, 191, 308
be_instance_of matcher, 308
be_kind_of matcher, 308
be_new_record matcher, 304
be_nil matcher, 308
be_non_empty matcher, 200
be_routable matcher, 304
be_success matcher, 86
be_truthy matcher, 191, 308
be_valid matcher, 304
be_within matcher, 177, 193, 309
Beck, Kent, 35, 38
before hooks
about, 113
configuring, 157
for data cleanup, 114
defined, 9
expect vs. allow, 268
Expense Tracker app examples, 72–73, 118
reducing duplication with, 72
scope, 117
behavior-driven development (BDD)
advantages, xv, 33–38
costs, 36–38