custom metadata, 134
customizing shared, 127
defined, 5
documentation formatter, 18
filtering by line numbers, 21, 147
focusing, 24
metadata, 88, 133
nesting, 16, 122, 126, 134
as Ruby classes, 11, 120
shared, 122–128, 158
:example hooks, 115, 117, 157
--example option
configuration options, 147
using, 21, 148
:example_group metadata key, 133
examples, *see also* example groups; metadata
aliasing, 111, 159
color coding, 7
creating, 108–109
custom metadata, 134
defined, 6
excluding/including, 138–139
expectations per, 87
filtering by line numbers, 21, 147
filtering temporarily, 139
focusing, 24
generated descriptions, 180–183
identifying slow, 20, 63
IDs, 92
measuring performance, 160
pending, 15, 26–29, 57, 141
running by name, 21, 148
running specific, 15, 20–26, 138–142, 148
sharing, 122, 124–128, 283
sharing setup, 8–13, 112–128
skipping, 29, 141
structure, 107–130
as term, 6
wording, 107–112
--exclude-pattern option, 147
exclusion filter (~), 139
exclusive ranges, 194, 309
exercises
acceptance specs, 59
advantages, xv
configuration, 165
custom matchers, 228–230
expectations, 183
Expense Tracker app, 78, 101, 143, 166
formatters, 31, 165
matchers, 183, 210–214, 228–230
metadata, 142
reducing duplication, 13, 78
running specs, 30
sharing code, 129
test doubles, 79, 246–249, 261–263, 291
unit specs, 78
exist matcher, 310
expect
vs. allow, 268
configuring responses, 251–255, 261
constraining arguments, 256
defined, 6
mocks, 238
partial doubles, 241, 252–253
vs. should, 171
using RSpec with other test frameworks, 296
expect() method, 52
expect_any_instance_of, 276
expect_with, 162
expectations, 169–183, *see also* matchers; messages
advantages, 173
vs. assertions, 173
configuration, 162
constraining arguments, 256–259, 261
defined, 6, 52, 169
diagram, 170
empty collections, 9
exercises, 183
installing, 4
negating, 9
parts, 170
per example, 87
readability, 169, 174
should syntax, 171
spies, 240
using RSpec with other test frameworks, 296
Expense Tracker app
acceptance specs, 49–59, 98
Bundler, 47, 294
checking account balance, 220–228
components, 45
configuration exercise, 166
connecting database, 82–84
custom matchers with helper methods, 216–218
custom matchers with matcher DSL, 220–228
data structure, 84
diagrams, 46, 61, 81
exercises, 78, 101, 143, 166
helper methods, 54, 121, 216–218
hooks, 72, 85, 92, 118
HTTP request/response cycle, 46, 49–62, 64–77
integration specs, 81–103
ledger, 65–77, 84–92, 243
metrics, 275–281
querying data, 54–57
querying expenses, 95–98
running, 98–101
saving expenses, 49–54, 64–77, 86–92
setup, 47
sharing code conditionally, 140
sharing contexts, 122–124
storage engine, 65–77
test doubles, 243
unit specs, 61–77
Explore It!, 38
extend, 141, 158

F

-f d option, 18
-f option, 18, 148, 160
f to focus, 24
factory methods, stubbing, 275–276, 281
failure messages, *see also* failures
aliases, 177
clarity, 173–174, 215
custom matchers, 215, 221
exercises, 210–214