example as alias for, 110
focusing, 24
skipping examples, 29
vs. specify, 110
specify as alias for, 110, 181
it_behaves_like, 122, 126–127

J

JetBrains, 22
:job specs, 303
JSON
exercises, 79
match matcher, 200
output option, 148
returning in Expense Tracker app, 53, 69

K

key-value pairs, matchers, 197
key-value store sharing example, 124–128
keyword arguments, 257
Kromer, Aaron, 218

L

last_response method, 52–56, 68–74, 78, 112
:last_run_status metadata key, 26, 133
layer boundaries, 68
Learn Ruby the Hard Way, xvii
ledger for Expense Tracker app, 65–77, 84–92, 94–98, 243
less-than comparison matchers, 191
let
sharing setup code with, 9, 13, 112
test doubles, 67
libraries
configuration, 161
excluding stack frames from, 63, 160
Expense Tracker app, 47, 82
installing, 4, 47, 82
loading, 146, 151
loading conditionally, 156
of matchers, 228
versions, xvii, 48, 293
line numbers, filtering examples by, 21, 147
$LOAD_PATH, 146, 151, 294
loading, conditionally, 94, 156
location, conventions, 125

M

:mailer specs, 303
manual exploratory testing, 38
Mario game example, 239, 241
marking work in progress, 15, 26–29, 57, 141
Marston, Myron, xvi, 283, 293
match matcher, 87, 197, 200, 202, 309
match method, 221, 223
match_array matcher, 309
match_regex matcher, 309
matcher, satisfy, 310
matcher DSL, 220–225, 228–229
matcher classes, 220, 225–228, 230
matchers, *see also* composable matchers; custom matchers
advantages, 174
aliases, 177, 218
attribute, 310
block, 187, 203–209, 311, 313
building matcher object, 174
case equality (===), 176, 190, 226, 259
cheat sheet, 307–314
as classes, 222
collection matchers flowchart, 201
collections, 180, 197–202, 309
comparison operators, 191–194, 308
compound, 176, 178, 219, 224, 226
defined, 170
delegating to with helper methods, 216–218
delta comparisons, 192–194, 309
duck typing, 310
dynamic predicates, 194–196, 199, 218, 310
embedding, 176, 178
equality, 52, 56, 171, 188–190, 307
exercises, 183, 210–214, 228–230
failure messages, 179–180, 215, 221, 223
as first-class objects, 174
fluent interface, 193, 203, 222
framework-independent, 228
generated descriptions, 180–183
hashes, 87, 96, 197, 258, 309
higher-order, 187, 190, 197–202, 205, 226
HTTP responses, 52–54
identity, 188–190, 307
libraries of, 228
match matcher, 87, 197, 200, 309
mutation, 207–209, 311
negating, 9, 174, 200, 209, 219, 221, 307, 311
nesting, 178, 180
object attributes, 202
as objects, 174, 176
order, 56, 201
output, 209, 312
passing into another, 176–177, 180, 224
primitive matchers, 187–196
Rails-specific, 304
raising and throwing, 203–205, 313
range comparisons, 192–194, 309
regular expressions, 201, 309, 313
satisfy, 196
strings, 197–202, 309
truthiness, 191, 308
understanding, 174–176
using, 171
value, 307
yield, 205, 207, 314
matches? method, 175, 226
memoization, 12
merge, 55
messages, *see also* error messages; failure messages
expectations, 238, 275
expecting on any instance, 275
mocks, 238