running
code selectively, 131
examples by name, 21, 148
failed specs only, xvi, 15, 21–24, 30, 131, 148, 159
Rack apps, 58, 98
selected examples, 15, 20–26, 138–142, 148
spec runner, 15–30
specs, 7, 15–30, 131, 138–142, 148

## S

SaaS example, 271–274
safety net, testing as a, 3
sales tax example, 287–290
sandwich example, 5–13
satisfy matcher, 196, 310
saving
expenses in Expense Tracker app, 49–54, 64–77, 86–92
progress with pending specs, 57
scenario, 302
scope, hooks, 113, 115–117
searching, *see* querying
--seed option, 90
separation, effective testing habits, 3
Sequel
automatic migrations, 84–86
configuring, 82–84
database transactions, 92–93
metadata exercise, 143
querying, 95–98
sequel command, 84
setter injection, 280
setup code
continuous integration, 249
running selectively, 131
sharing, 8–13, 112–130
shared example groups, 122–128, 158
shared_context, 122–123
shared_examples, 122, 125–128
sharing
code conditionally, 140
code with modules, 157
contexts, 122–124
example groups, 122–128, 158
examples, 122, 124–128, 283
setup code, 8–13, 112–130
Shaw, Zed, xvii
Shay, Xavier, 62
shells
bash, 99
escaping ~, 140
shell sessions, xiv
should, 171, 181
should_not, 171, 181
Shoulda Matchers library, 228
side effects, mocks, 238
signup example, 266–268
Sinatra, 46–48, 59, 70, 102
skiing example, 246–249
skip, 29
:skip tag, 141
skipping, examples, 29, 141
sliming the test, 54
Software as a Service (SaaS) example, 271–274
sort method, 213
sorting, collections, 213
spec runner, 15–30
spec/support folder, 85, 125
spec_helper.rb file, 48, 59, 63, 85, 90, 93, 115, 135, 139, 150, 156, 217, 248, 274, 300
SPEC_OPTS environment variable, 150, 296
specifications, *see* specs
specify, 110, 181
specs, *see also* acceptance specs; integration specs; pending specs; unit specs
confirming spec can fail, 71
defined, 5–6
focusing, 24
guidelines, 40
ordering, 141–142
output as documentation, 15, 18, 36, 149, 296
Rails types, 301–304
resources on, 62
running, 7, 15–30, 131, 138–142, 148
running failed only, xvi, 15, 21–24, 30, 131, 148, 159
running specific, 15, 20–26, 138–142, 148
simple example, 5–13
skipping, 29
spec runner, 15–30
as term, 6
types, 39–40, 62, 301–304
spies, *see also* test doubles
converting to, 271
defined, 234
partial doubles as, 242, 271
pure doubles as, 242, 271
as term, 67
using, 239
verifying doubles as, 244
splat operator, 198–199
Spring, 300
_spy variant for verifying doubles, 244
SQL
metadata exercise, 142
SQLite library, 82–84
--standalone option for Bundler, 294
start_with matcher, 179, 197–199, 202, 309
statistics example, 275–281
stock ticker circuit breaker example, 259
storage, Expense Tracker app, 65–77
StringIO, faking with, 284–286
strings
failure message, 28
higher-order matchers, 197–202
matchers, 197–202, 309
name issues, 247
Stuart, Tom, ix–x, 280
stub_const, 245, 254, 278
stubbed constants
connecting test subject to environment, 275, 278, 281
defined, 234
using, 244, 254, 278
stubject, 268–271
stubs, *see also* test doubles
creating, 236