defined, 234
messages, 236
modifying return value, 254
stubject, 268–271
as term, 67
uses, 236
subclassing, 276
subject method, 182
subjects
connecting to test environment, 274–281
defined, 170
expectations, 170, 182
stubbing, 268–271
wrapping with expect, 171
Sublime Text, 22
subscription service example, 271–274
:suite hooks, 85, 116, 157
super keyword, 222
sustainability, 35
symbols, thrown, 203, 205
syntax highlighting, 19, 47

T

-t option, 147
--tag option, 26, 135, 139, 147
tags, *see also* metadata
database transactions, 93, 143
derived metadata, 135, 159
excluding/including examples, 138–139
filtering temporarily, 139
filtering with, 25, 138–139, 147
TaxJar example, 287–290
TDD, *see* test-driven development (TDD)
tea example, 30
teardown, *see also* cleanup
partial doubles, 242
test doubles, 242
test cases, *see* examples
test doubles, 233–249, *see also* fakes; mocks; partial doubles; pure doubles; spies; stubs; verifying doubles
about, 231
advantages, 233
blocks, 255, 261–263
configuration, 161–162, 248, 274
configuring responses, 251–255, 261
connecting test subject to environment, 274–281
constraints, 254–260, 262–263
creating, 235
Cucumber, 297
customizing, 251–263
decoupling with, 267
defined, 67
dependency injection, 274–275, 279–281, 287
disadvantages, 265
exercises, 79, 246–249, 261–263, 291
fluent interface, 263
generic, 235
instances, 67
ledger for Expense Tracker app, 67–69
limitations, 285
modifying return value, 254
multiple, 236
nesting, 288
ordering, 260–261
origins, 234, 241–245
performance, 247
raising errors, 251, 253
resources on, 67, 162, 251, 288, 291
returning multiple values, 252
stand-alone mode, 235, 238
stubject, 268–271
terms, 233–235
test environment, 265–269, 274–281
third-party code, 281–290
tweaking arguments, 254
types, 233–235
usage modes, 234–241
"Test Doubles", 67
test frameworks
Cucumber, 296–297
Minitest, xvi, 163, 174, 228, 296
using parts of RSpec with other, 296–297
"Test Isolation Is About Avoiding Mocks", 288
test-driven development (TDD), *see also* behavior-driven development (BDD)
advantages, xv, 33–38
expectations per example, 87
listening to tests, ix
Red/Green/Refactor practice, 8, 94
as term, xv
Test::Unit, 228
"Testing Sinatra with Rack::Test", 59
tests, *see also* effective testing; specs; test-driven development (TDD)
defined, 6
manual exploratory testing, 38
overtesting, 37
as term, 6
what not to test, 38
text editors, 22
third-party code
marking as pending, 29
test doubles, 281–290
ThoughtBot, 22
throw_symbol matcher, 203, 205, 313
throwing
matchers, 203–205, 313
test doubles, 251
ticketing app example, 215, 228–230
tilde (~) for exclusion filter, 139
times method, 206, 259
to, 52
as change matcher modifier, 208
custom matchers, 221
failure messages, 173
negating, 9, 172
to_not, 172, 219, 307, 311
to_stderr modifier, 209, 312
to_stderr_from_any_process modifier, 209, 312
to_stdout modifier, 209, 312
to_stdout_from_any_process modifier, 209, 312
toaster example, 12
tokenizer exercise, 212
transactions, database, 92–93, 140, 143