```
$ rspec spec/unit spec/smoke       # Load more than one directory
$ rspec spec/unit spec/foo_spec.rb # Or mix and match files and directories
```

Not only can you load specific files or directories, you can also filter which of the loaded examples RSpec will actually run. Here, we'll explore a few different ways to run specific examples.

Running Examples by Name

Rather than running all the loaded specs, you can choose a specific example by name, using the --example or -e option plus a search term:

```
$ rspec -e milk -fd
Run options: include {:full_description=>/milk/}

A cup of coffee
  with milk
    costs $1.25 (FAILED - 1)

Failures:

  1) A cup of coffee with milk costs $1.25
     Failure/Error: expect(coffee.price).to eq(1.25)

       expected: 1.25
            got: 1.0

       (compared using ==)
     # ./spec/coffee_spec.rb:26:in `block (3 levels) in <top (required)>'

Finished in 0.01014 seconds (files took 0.08249 seconds to load)
1 example, 1 failure

Failed examples:

rspec ./spec/coffee_spec.rb:25 # A cup of coffee with milk costs $1.25
```

RSpec ran just the examples containing the word *milk* (in this case, just one example). When you use this option, RSpec searches the full description of each example; for instance, A cup of coffee with milk costs $1.25. These searches are case-sensitive.

Running Specific Failures

Often, what you really want to do is run just the most recent failing spec. RSpec gives us a handy shortcut here. If you pass a filename and line number separated by a colon, RSpec will run the example that starts on that line.

You don't even have to manually type in which file and line to rerun. Take a look at the end of the spec output: