```
$ rspec
.F

« truncated »

2 examples, 1 failure

Failed examples:

rspec ./spec/coffee_spec.rb:25 # A cup of coffee with milk costs $1.25
```

You can copy and paste the first part of that final line (before the hash) into your terminal to run just the failing spec. Let's do so now:

```
$ rspec ./spec/coffee_spec.rb:25
Run options: include {:locations=>{"./spec/coffee_spec.rb"=>[25]}}
F

« truncated »

1 example, 1 failure

Failed examples:

rspec ./spec/coffee_spec.rb:25 # A cup of coffee with milk costs $1.25
```

RSpec ran only the single example you specified. This focusing ability becomes even more powerful when you add a key binding for it to your text editor. Several IDEs and editor plugins provide this behavior for you, including the following:

- ThoughtBot's rspec.vim plugin[2]
- Peter Williams's RSpec Mode for Emacs[3]
- The RSpec package for Sublime Text[4]
- Felipe Coury's Atom RSpec Runner[5]
- The RubyMine IDE from JetBrains[6]

With good editor support, you can quickly run the example under your cursor with a single keystroke.

Use Editor Integration for a More Productive Experience



Having to switch back and forth between your editor and a terminal window in order to run rspec really interrupts your workflow. We recommend taking the time to install an editor plugin so that running rspec is only a keystroke away.

2. https://github.com/thoughtbot/vim-rspec
3. https://www.emacswiki.org/emacs/RspecMode
4. https://github.com/SublimeText/RSpec
5. https://github.com/fcoury/atom-rspec
6. https://www.jetbrains.com/ruby/