Rerunning Everything That Failed

Using a line number works well when only one spec is failing. If you have more than one failure, you can run all of them with the --only-failures flag. This flag requires a little bit of configuration, but RSpec will coach you through the setup process:

```
$ rspec --only-failures

To use `--only-failures`, you must first set                    ↩
`config.example_status_persistence_file_path`.
```

RSpec needs a place to store information about which examples are failing so that it knows what to rerun. You supply a filename through the RSpec.configure method, which is a catch-all for lots of different runtime options.

Add the following lines to your coffee_spec.rb file between the Coffee class definition and the specs:

02-running-specs/06/spec/coffee_spec.rb

```
RSpec.configure do |config|
  config.example_status_persistence_file_path = 'spec/examples.txt'
end
```

You'll need to rerun RSpec once without any flags (to record passing/failing status):

```
$ rspec
.F

« truncated »

2 examples, 1 failure

Failed examples:

rspec ./spec/coffee_spec.rb:29 # A cup of coffee with milk costs $1.25
```

Now, you can use the --only-failures option:

```
$ rspec --only-failures
Run options: include {:last_run_status=>"failed"}
F

« truncated »

1 example, 1 failure

Failed examples:

rspec ./spec/coffee_spec.rb:29 # A cup of coffee with milk costs $1.25
```

Let's see what happens when the behavior gets fixed and the specs pass. Take a swing at modifying the Coffee class to pass both examples. Here's one possible implementation: