Let's see what that looks like with the "A cup of coffee with milk costs $1.25" example. In coffee_spec.rb, replace context with fcontext (think of it as shorthand for *focused context*):

02-running-specs/07/spec/coffee_spec.rb
```
fcontext 'with milk' do
```

Next, we need to configure RSpec to run just the focused examples. Edit the RSpec.configure block in this file and add the following highlighted line:

02-running-specs/07/spec/coffee_spec.rb
```
RSpec.configure do |config|
  config.filter_run_when_matching(focus: true)
  config.example_status_persistence_file_path = 'spec/examples.txt'
end
```

Now, when you run just rspec, it'll run only the example in the focused context:

```
$ rspec
Run options: include {:focus=>true}
.

Finished in 0.00093 seconds (files took 0.07915 seconds to load)
1 example, 0 failures
```

If you haven't marked any specs as focused, RSpec will run all of them.

We'd like to show you one more aspect of focused specs. Take a look at the first line of the output:

```
Run options: include {:focus=>true}
```

We saw something similar in the section on running only failed examples:

```
Run options: include {:last_run_status=>"failed"}
```

Although these two ways of slicing and dicing your specs feel very different, they're both built on the same simple abstraction.

Tag Filtering

Earlier, when you wrote the following line to focus on the with milk context:

02-running-specs/07/spec/coffee_spec.rb
```
fcontext 'with milk' do
```

…this code was really just shorthand for the following expression:

02-running-specs/08/spec/coffee_spec.rb
```
context 'with milk', focus: true do
```