Getting Started

You've already installed RSpec for a few stand-alone experiments. But this project has more dependencies than just RSpec. Customers deploying our app will want to use the exact same versions of Ruby gems we've tested with.

For this app, we'll use Bundler to catalog and install all the libraries we depend on.[3] If you've never used Bundler, don't worry; while we won't be explaining it in depth, you won't need any prior experience with it to follow along.

Create a new directory called expense_tracker. From there, install Bundler the same way you'd install any Ruby gem, and then run bundle init to set your project up to use Bundler:

```
$ gem install bundler
Successfully installed bundler-1.15.3
1 gem installed
$ bundle init
Writing new Gemfile to ~/code/expense_tracker/Gemfile
```

We'll need four Ruby libraries to get started:

- RSpec to test our project
- Coderay for easy-to-read, syntax-highlighted failure output
- Rack::Test to provide an API for driving web services from tests
- Sinatra to implement the web application; its light footprint and simple API are a good fit for this project

To bring these dependencies into the project, add the following lines to the end of the newly generated Gemfile:

04-acceptance-specs/01/expense_tracker/Gemfile

```
gem 'rspec',     '3.6.0'
gem 'coderay',   '1.1.1'
gem 'rack-test', '0.7.0'
gem 'sinatra',   '2.0.0'
```

Then, tell Bundler to install the required libraries and their dependencies:

```
$ bundle install
Fetching gem metadata from https://rubygems.org/.........
Fetching version metadata from https://rubygems.org/..
Resolving dependencies...
Using bundler 1.15.3
Using coderay 1.1.1
Using diff-lcs 1.3
Fetching mustermann 1.0.0
```

3. http://bundler.io