```
$ bundle exec rspec spec/unit/app/api_spec.rb
« truncated »

Failures:

  1) ExpenseTracker::API POST /expenses when the expense is successfully ↩
  recorded returns the expense id
     Failure/Error: expect(parsed).to include('expense_id' => 417)

       expected {"expense_id" => 42} to include {"expense_id" => 417}
       Diff:
       @@ -1,2 +1,2 @@
       -"expense_id" => 417,
       +"expense_id" => 42,

     # ./spec/unit/app/api_spec.rb:30:in `block (4 levels) in ↩
     <module:ExpenseTracker>'

Finished in 0.03784 seconds (files took 0.16365 seconds to load)
4 examples, 1 failure, 3 pending

Failed examples:

rspec ./spec/unit/app/api_spec.rb:20 # ExpenseTracker::API POST /expenses ↩
when the expense is successfully recorded returns the expense id

Randomized with seed 56373
```

Once you have a failing spec, it's time to fill in the implementation.

Handling Success

To pass this spec, the /expenses route of our API needs to do three things:

- Parse an expense from the request body
- Use its Ledger (either a real database-based one or a fake one for testing) to record the expense
- Return a JSON document containing the resulting expense ID

Change your /expenses route inside app/api.rb to the following code:

05-unit-specs/03/expense_tracker/app/api.rb

```
post '/expenses' do
  expense = JSON.parse(request.body.read)
  result = @ledger.record(expense)
  JSON.generate('expense_id' => result.expense_id)
end
```

Now, rerun the specs:

```
$ bundle exec rspec spec/unit/app/api_spec.rb
« truncated »
```