```
     Failure/Error: expect(parsed).to include('error' => 'Expense
     incomplete')

       expected {"expense_id" => 417} to include {"error" => "Expense
       incomplete"}
       Diff:
       @@ -1,2 +1,2 @@
       -"error" => "Expense incomplete",
       +"expense_id" => 417,

     # ./spec/unit/app/api_spec.rb:52:in `block (4 levels) in
     <module:ExpenseTracker>'

  2) ExpenseTracker::API POST /expenses when the expense fails validation
  responds with a 422 (Unprocessable entity)
     Failure/Error: expect(last_response.status).to eq(422)

       expected: 422
            got: 200

       (compared using ==)
     # ./spec/unit/app/api_spec.rb:57:in `block (4 levels) in
     <module:ExpenseTracker>'

Finished in 0.03552 seconds (files took 0.13746 seconds to load)
4 examples, 2 failures

Failed examples:

rspec ./spec/unit/app/api_spec.rb:48 # ExpenseTracker::API POST /expenses
when the expense fails validation returns an error message
rspec ./spec/unit/app/api_spec.rb:55 # ExpenseTracker::API POST /expenses
when the expense fails validation responds with a 422 (Unprocessable entity)

Randomized with seed 8222
```

The POST route needs to check the success? flag of the RecordResult and set the HTTP status and body accordingly. Open up app/api.rb and change the post '/expenses' route to the following:

05-unit-specs/07/expense_tracker/app/api.rb

```
post '/expenses' do
  expense = JSON.parse(request.body.read)
  result = @ledger.record(expense)

  if result.success?
    JSON.generate('expense_id' => result.expense_id)
  else
    status 422
    JSON.generate('error' => result.error_message)
  end
end
```