Rerun your specs, and make sure they pass. Then, go back and take a peek at the latest iteration of your unit specs. Notice how the test doubles define the interface that the Ledger class needs to provide. Before we finish off this chapter, let's sketch out the Ledger class.

## Defining the Ledger

We'll start with an empty Ledger class. In your project directory, create a new file called app/ledger.rb with the following contents:

05-unit-specs/08/expense_tracker/app/ledger.rb

```
module ExpenseTracker
  RecordResult = Struct.new(:success?, :expense_id, :error_message)

  class Ledger
  end
end
```

Notice we've also moved the temporary RecordResult struct definition from earlier into its permanent home here. Don't forget to delete the old version of RecordResult from spec/unit/app/api_spec.rb.

You'll need to require this new file from app/api.rb:

05-unit-specs/08/expense_tracker/app/api.rb

```
require_relative 'ledger'
```

The specs you have so far are still using the fake ledger. They passed without a real Ledger class defined, so you might expect them to keep passing now that we have one. Go ahead and try it:

```
$ bundle exec rspec spec/unit/app/api_spec.rb
« truncated »

Failures:

  1) ExpenseTracker::API POST /expenses when the expense is successfully ↩
  recorded returns the expense id
     Failure/Error:
       allow(ledger).to receive(:record)
         .with(expense)
         .and_return(RecordResult.new(true, 417, nil))

       the ExpenseTracker::Ledger class does not implement the instance ↩
       method: record
     # ./spec/unit/app/api_spec.rb:19:in `block (4 levels) in ↩
     <module:ExpenseTracker>'

« truncated »

Finished in 0.00783 seconds (files took 0.13142 seconds to load)
4 examples, 4 failures
```