Hooking Up the Database

We've put off implementing the database layer for as long as we could. But with the rest of the surrounding layers defined, it's all that's left.

Getting to Know Sequel

For this exercise, you're going to use a Ruby database library called Sequel. Sequel allows you to create tables, add data, and so on, without tying your code to any specific database product. You'll still need to *choose* a database, though, and for this project the low-maintenance SQLite library will do fine.[1]

Go ahead and add the following two lines to your Gemfile:

06-integration-specs/01/expense_tracker/Gemfile

```
gem 'sequel',    '4.48.0'
gem 'sqlite3',   '1.3.13'
```

Now, rerun Bundler to install the new libraries:

```
$ bundle install
Fetching gem metadata from https://rubygems.org/.........
Fetching version metadata from https://rubygems.org/..
Resolving dependencies...
Using bundler 1.15.3
Using coderay 1.1.1
Using diff-lcs 1.3
Using mustermann 1.0.0
Using rack 2.0.3
Using rspec-support 3.6.0
Fetching sequel 4.48.0
Installing sequel 4.48.0
Using tilt 2.0.7
Fetching sqlite3 1.3.13
Installing sqlite3 1.3.13 with native extensions
Using rack-protection 2.0.0
Using rack-test 0.7.0
Using rspec-core 3.6.0
Using rspec-expectations 3.6.0
Using rspec-mocks 3.6.0
Using sinatra 2.0.0
Using rspec 3.6.0
Bundle complete! 6 Gemfile dependencies, 16 gems now installed.
Use `bundle info [gemname]` to see where a bundled gem is installed.
```

Once Sequel and SQLite are installed, you're ready to use them. In our application, you'll eventually do the following:

1. https://sqlite.org