CompleteOrderJob jobs. The second time period shows that the CompleteOrderJob for order #1 has been processed and the SendOrderNotificationEmailJob and RequestOrderFulfillmentJobs have been placed on the default queue. The third time period shows a third CompleteOrderJob queued in the high queue, right behind the job for order #2.

You'll recall that the value queues: from config/sidekiq.yml is an array. The ordering is what Sidekiq uses to determine priority, so to create a queue with higher priority than the default queue, you can add the queue's name as the first element in this list, like so:

snapshots/4-2/sidekiq-book/config/sidekiq.yml

```
:concurrency: <%= ENV.fetch("SIDEKIQ_CONCURRENCY") { 5 } %>
:timeout: <%= ENV.fetch("SIDEKIQ_TIMEOUT_SECONDS") { 25 } %>
:queues:
  - high
  - default
```

To use this queue, modify CompleteOrderJob to use sidekiq_options to set the queue to use:

snapshots/4-2/sidekiq-book/app/jobs/complete_order_job.rb

```
class CompleteOrderJob
  include Sidekiq::Job

  sidekiq_options queue: "high"

  def perform(order_id)
    order = Order.find(order_id)
    OrderCreator.new.complete_order(order)
  rescue BaseServiceWrapper::HTTPError => ex
    raise IgnorableExceptionSinceSidekiqWillRetry.new(ex)
  end
end
```

With this in place, restart your server, create an order, and visit the Sidekiq Web UI. Click on "Queues" and you should see the high queue (as in the screenshot that follows).