As you can see from the screenshot, Devise generates two new files in your Rails application. Those two files are:

- `devise.rb`: This file is located at `config/initializers/devise.rb` and will be used as the Devise main configuration file.
- `devise.en.yml`: This file is located at `config/locales/devise.en.yml` and it will be used as an internationalization file for English language.

Not just generating files, the installation command also prints some information that will be useful for our complete Devise setup. This information will tell us about:

- The basic URL configuration that applies to every environment setting. The code shown in the screenshot should be added to the environment settings, so that Devise will acknowledge the application URL which is used in its autogenerated e-mail. Especially for production, the host value should be filled with your actual application domain.
- The route setting that you need to add to your `config/routes.rb` file. By defining your root URL, Devise will use it for its redirection. For example, Devise will redirect the user to the root URL after they sign out from the application.
- Devise helpers that can be used to generate errors or warning messages when there's something wrong with the code. This is very useful and you can write it in your views file.
- Configuration that you need to add when deploying to Heroku. I'm not going to discuss about it in this book.
- How to generate copies of Devise views, so that you can customize it later. We will see how it works in *Chapter 2*, *Authenticating Your Application with Devise*.

The next step is generating a Devise model. Let's name our Devise model as **user**. For your information, this model name can be replaced with any name you wish. This name also determines the Devise helper's name. We will see how we use it later in this chapter. To generate the Devise model, you can execute the following command:

```
$ rails generate devise user
```


www.it-ebooks.info