You need to define the connection settings in your application. Because we are in the development environment, you can open the `config/environments/development.rb` file and add this code:

```
config.action_mailer.delivery_method = :smtp
config.action_mailer.perform_deliveries = true
config.action_mailer.raise_delivery_errors = true
config.action_mailer.smtp_settings = {
  :address => "smtp.gmail.com",
  :port => 587,
  :domain => "gmail.com",
  :user_name => <your_gmail_user_name>,
  :password => <your_gmail_password>,
  :authentication => 'plain',
  :enable_starttls_auto => true
}
```

Next, modify your `model` file and add a module, so your `model` file will be as follows:

```
class User < ActiveRecord::Base
    devise :database_authenticatable, :registerable, :recoverable,
    :rememberable, :trackable, :validatable, :confirmable
end
```

It's almost done. Now, create a migration file and modify it so that the content will be as follows:

```
class AddConfirmableToUsers < ActiveRecord::Migration
  def up
    add_column :users, :unconfirmed_email, :string
    add_column :users, :confirmation_token, :string
    add_column :users, :confirmed_at, :string
    add_column :users, :confirmation_sent_at, :datetime

    add_index :users, :confirmation_token, :unique => true

    User.update_all(:confirmed_at => Time.now) #your current data
will be treated as if they have confirmed their account
  end

  def down
    remove_column :users, :unconfirmed_email,
    :confirmation_token, :confirmed_at, :confirmation_sent_at
  end
end
```


www.it-ebooks.info