Integrating Devise with Mongoid

This is an example of how you are able to implement Devise with one of the NoSQL databases, such as MongoDB. To establish a connection, we are going to use **Mongoid** as a driver. I'm going to show you two examples. The first example will require a fresh Rails application where you need to generate a new Rails application, and the second one will show you how to change the configuration from MySQL to MongoDB. Note that these examples will use MongoDB Version 2.2.0 and I will not tell you how to install MongoDB, but you can see the full documentation about its installation at `http://docs.mongodb.org/manual/installation/`. As you can see in the documentation, it also shows you how to turn on the server; therefore, I assume you have done it before you proceed to the next step.

Now, we can start from the first example by executing the Rails application generation command without specifying the database type:

```
$ rails new learning-devise-mongoid
```

Next, you need to add two new gems inside `Gemfile` and after you have added them, you can install them by executing `bundle install`:

```
gem 'mongoid'
gem 'devise'
```

Now, you need to create a configuration file for Mongoid by executing the following command:

```
$ rails generate mongoid:config
```

In my case, I don't need to change anything in my Mongoid configuration. But, if you want to see the content of the configuration file or you need to change something in it, you can open the file at `config/mongoid.yml`.

Since we are no longer using active record, we need to modify the `config/application.rb` file and remove the line, `require 'rails/all'`, while adding this code:

```
require 'action_controller/railtie'
require 'action_mailer/railtie'
require 'rails/test_unit/railtie'
require 'sprockets/railtie'
```

You also need to modify one of the files in `config/environments`; for this example, we are going to modify `development.rb` because we are currently in the development environment. Please remove or comment out this line of code:

```
config.active_record.migration_error = :page_load
```


www.it-ebooks.info