```
<%# using cannot? %>
<%# Typically, can? is used a lot more than cannot? %>

<% if cannot?(:destroy, post) %>
  <p>It looks like you cannot delete this post. If you want this
post to be deleted, please contact the administrator or the
owner.</p>
<% end %>
```

Run the Rails server by executing `rails s` in your terminal, and open `http://localhost:3000` in your browser to see if the destroy link is visible for logged-in users, the post creator, or guest users.

9. Restricting controller access based on the defined rules: You restricted views accordingly, and you noticed that someone could just use the URL (via CURL, for example) to delete the post. This leads to the need of authorization check controllers.

   CanCan provides a few authorization-related methods in controllers. One of the most frequently used methods is `authorize!`, which accepts two arguments, an action name, and a resource. The method raises the `CanCan::AccessDenied` exception when the currently logged-in user's privileges are not enough to perform the action on the resource.

   For example, we can check for a current user's privileges on creating a new post and destroying an existing post as follows:

```
class PostsController < ApplicationController
  before_action :set_post, only: [:show, :edit,
    :update, :destroy]
  # ...

  def new
    authorize! :new, Post
    # codes for new...
  end
  # ...

  def destroy
    authorize! :destroy, @post
    @post.destroy
    # ...
  end
end
```


www.it-ebooks.info