Just to remind you, the consumer key and the consumer secret are our application's "username"' and "password" for Twitter's remote authentication, respectively. It is very important to keep both keys safe.

```
config.omniauth :twitter, 'CONSUMER_KEY', 'CONSUMER_SECRET'
```



Remember that changes in any file within the `config/initializers` folder require an application restart. Don't forget to restart your application server after modifying Devise initializers.

By specifying the preceding configuration, Devise will also generate helpers for linking to the Twitter authentication, `user_omniauth_authorize_path(:twitter)`. This is assuming our model name that utilizes Devise is called `User`; if you use any other name, the helper will change accordingly. We can use the helpers in our home page or sign-in page like this:

```
<%= link_to "Sign in with Twitter", user_omniauth_authorize_
path(:twitter) %>
```

When users click on the link that was generated by the previously mentioned helper, they will be greeted by the Twitter application authorization page. This will only happen during their first visit; subsequent visits will instantly redirect back to our application after Twitter finishes authenticating our credentials. At the application authorization page, they will have to either authorize our application, or reject, in which case, they won't be able to sign in.

Up until this point, if we try to sign in using Twitter in our application and we choose to authorize it in the Twitter application authorization page, we will be redirected back but will see a "route does not exist" error page. This is normal because we haven't prepared appropriate routes, controllers, and views to handle the redirection.

Let's create it by using the Rails generator command (abbreviated `g`).

```
$ rails g controller omniauth_callbacks
```

Now, we have to tell Devise that the newly-generated controller will be the one that handles callbacks. To do that we can modify the existing `devise_for` routes by following the syntax in the following example:

```
devise_for :users, controllers: {omniauth_callbacks: "omniauth_
callbacks"}
```


www.it-ebooks.info