Devise will automatically generate routes that link the callback URL of our application (the URL that will be supplied to the `oauth_callback` parameter) with a controller that will handle the callback logic. You can see the generated routes as follows:

```
user_omniauth_authorize GET|POST /users/auth/:provider(.:format)
omniauth_callbacks#passthru {:provider=>/twitter|facebook/}

user_omniauth_callback GET|POST /users/auth/:action/callback(.:format)
omniauth_callbacks#(?-mix:twitter|facebook)
```

The next step, is to modify OmniAuth callbacks that have been generated earlier. Devise has a class that we can inherit from; it's called `Devise::OmniauthCallbacks Controller`. So, let's inherit from it and specify our first action, `twitter`.

```
class OmniauthCallbacksController < Devise::OmniauthCallbacksControll
er
  def twitter
  end
end
```

Do you remember that users will be redirected back to our application after they authorize it in the Twitter authorization page? During the redirection, Twitter will actually supply extra information that we can parse and utilize for our sign-in process. This information is retrieved, processed, and stored by OmniAuth within the `request.env` hash using `omniauth.auth` as the key.

Let's inspect it by raising it in our callbacks controller.

```
class OmniauthCallbacksController < Devise::OmniauthCallbacksControll
er
  def twitter
    raise request.env["omniauth.auth"].to_yaml
  end
end
```

After specifying the raise, try to raise it by clicking on the sign-in using the Twitter link and authorize your application in the Twitter authorization page. We will see an exception page that shows all the authentication information that was given by Twitter.

www.it-ebooks.info