Now, let's start writing our test code from the unit test. Please add a new file named `users_spec.rb` under `spec/models/`. If you don't have a folder named `models`, you can create it on your own and save the file under that folder. Referring to the `user.rb` file written in *Chapter 4*, *Remote Authentication with Devise and OmniAuth*, we have a method called `process_omniauth`, and we will create our test case in that method. Please write the following code inside `users_spec.rb`:

```
require 'spec_helper'

describe User do
it "processes omniauth from existing user" do
auth = {
:provider => "twitter",
:uid => "1234567",
:info => {
:nickname => "hafizbadrie"
}
}
user = FactoryGirl.create(:user)
tested_user = User.process_omniauth(auth)

expect(tested_user).to eq(user)
end

it "processes omniauth with new user" do
auth = {
:provider => "twitter",
:uid => "1234567",
:info => {
:nickname => "hafizbadrie"
}
}
tested_user = User.process_omniauth(auth)
expect(tested_user.persisted?).to be_false
end
end
```

You just defined two test cases for the `process_omniauth` method. The first test case shows that the method processing the data defined by `auth` is equal to the data existing in the database, while the second shows the opposite of this, that is, the data defined by `auth` is new. As you can see, the method used by RSpec is different from the ones we used in previous examples. For more information about the methods, you can go to the following original documentation sites:

- `http://rubydoc.info/gems/rspec-core`
- `http://rubydoc.info/gems/rspec-expectations`

www.it-ebooks.info