Using Values

Our code is pretty simple so far, but it's still missing a bit of functionality. We're not yet changing the text of the button from "Hide" to "Show." On a more structural level, we don't have a place in the code that explicitly stores the state of the button. We have to infer the state from the presence or absence of the `hidden` class, which is not a terrible thing to have to do, but it's often better to explicitly have the state of the system available.

We can do all of these things using another Stimulus concept: *values*. In Stimulus, values are a bit of syntactic sugar that allow us to use data attributes to store data that is specifically associated with a controller, and gives the controller some methods to manipulate that data directly without dealing with the DOM dataset itself.

To declare a value, we use a similar pattern to what we've been using for targets. The attribute name itself has multiple parts: `data-`, the dash-case controller name followed by another hyphen (`-`), the name of the attribute, then `-value`.

We want to start with one data HTML attribute for the visibility state of the element. This means our attribute name will be `data-favorite-toggle-visible-value`. Note that in this case, the attribute name is in dash-case in the HTML but will be camelCase in the JavaScript.

You typically add the value attributes to the same DOM element that declares the controller, though technically they can be attached to any DOM element inside the controller. Most of the time you want them with the controller declaration so that the data references are easy to find. That gives us:

chapter_03/05/app/views/favorites/_list.html.erb

```
<section
  class="my-4"
  data-controller="favorite-toggle"
  data-favorite-toggle-visible-value="true">
```