what the Show/Hide button looks like in the favorites list:

chapter_03/08/app/views/favorites/_list.html.erb

```
<%= turbo_frame_tag("favorite-concerts") do %>
 <section
    class="my-4"
    data-controller="css"
    data-css-css-class="hidden"
    data-css-status-value="false">
  <div class="text-3xl font-bold">
    Favorite Concerts
    <button
      class="<%= SimpleForm.button_class %> py-1 text-xl font-semibold"
      data-controller="text"
      data-text-target="elementWithText"
      data-text-status-value="false"
      data-text-off-value="Hide"
      data-text-on-value="Show"
      data-action="click->css#toggle click->text#toggle">
    </button>
  </div>
  <div data-css-target="elementToChange">
    <div class="text-xl font-bold" id="no-favorites">
      <% if current_user.favorites.empty? %>
        No favorite concerts yet
      <% end %>
    </div>
    <div id="favorite-concerts-list">
      <% current_user.favorites.each do |favorite| %>
        <%= render(favorite) %>
      <% end %>
    </div>
  </div>
 </section>
<% end %>
```

The outer section declares the css controller and specifies that it will use hidden as the class to toggle. The inner span for the actual button declares the text controller, the off value of “Hide”, and the on value of “Show”. The button also declares itself as the target of the text controller, meaning it is the element whose text changes, and it declares that clicking on it triggers the toggle action in both the