CSS and text controllers. Below that, the div surrounding the actual value declares itself the target of the CSS controller, meaning it is the element that gets the hidden class added and removed from it. One other change here is that the button does not actually have HTML text in it—the Stimulus controller will call its statusValueChanged method when it connects and will set the text for us.

This works, and we can now adapt it around the page.

We can add a similar structure to the buttons for each day of the schedule, allowing those to be shown or hidden:

chapter_03/08/app/views/schedule_days/_schedule_day.html.erb

```
<section
  data-controller="css"
  data-css-css-class="hidden"
  data-css-status-value="false">
 <h2 class="text-3xl font-bold">
  <%= schedule_day.day.by_example("Monday, January 2, 2006") %>
  <span
    class="<%= SimpleForm.button_class %> py-1 text-xl font-semibold"
    data-controller="text"
    data-text-target="elementWithText"
    data-text-status-value="false"
    data-text-off-value="Hide Day"
    data-text-on-value="Show Day"
    data-action="click->css#toggle click->text#toggle">
  </span>
 </h2>
 <% if show %>
  <section data-css-target="elementToChange">
   <% schedule_day.concerts.sort_by(&:start_time).each do |concert| %>
    <%= render(concert) %>
   <% end %>
  </section>
 <% end %>
</section>
```

This has nearly the same structure, with an outer element declaring the CSS controller and an inner button declaring the text controller and the actions. This now also works, with no additional JavaScript.