Installing React

We're going to use React to build up the individual pages for each concert. These pages will contain a seating diagram and will allow you to put together a ticket order. Normally I wouldn't use Stimulus and React in the same app—I'd pick one and stick with that choice—but it's far from the most ridiculous thing I've ever done in an app, and I decided that keeping them together would be less confusing than trying to keep track of separate Stimulus and React apps.

Our JavaScript build system is already set up to handle React if React is installed—esbuild handles React files out of the box. So let's install React:

```
$ yarn add react react-dom @babel/preset-react @types/react @types/react-dom
```

This command adds several packages to the package.json file. In addition to the react package, we get react-dom, which contains React's DOM-specific features. We get a Babel package, which allows some JavaScript build tools to compile JSX files. We also get the @types packages, which contain TypeScript definitions for React and React-DOM (I'll talk more about what these modules contain in Chapter 13, *Validating Code with Advanced TypeScript*).

We need to change the tsconfig.json file to include the line:

```
"jsx": "react",
```

which makes that file look like this:

chapter_04/01/tsconfig.json

```
{
  "compilerOptions": {
    "declaration": false,
    "emitDecoratorMetadata": true,
    "experimentalDecorators": true,
    "lib": ["es2019", "dom"],
    "jsx": "react",
    "module": "es6",
    "moduleResolution": "node",
```