Composing Components

Now that we have a component for each seat, we want to combine multiple seats into a row and then combine multiple rows into a venue. Invoking a component from another component normally involves a JSX call that looks as though the component was an HTML tag with the name of the component first and the props following with the same syntax used to write HTML attributes.

So if we want to use our `Seat` component, we'd call it with syntax like `<Seat seatNumber={seatNumber} />`. The first part of the tag is our component name, and then we assign the prop as if it were an HTML attribute using the curly bracket notation to send the value of the seat number. If the value being sent is a string, you can use a string literal rather than the brackets, as in `<Seat description="front row center" />`.

We don't want to add just one `Seat`, though; we want to add an entire row of them. For the moment, we can assume that the seat numbers are just incremental integers, but even so, our `Row` component needs to create a `Seat` component corresponding to each seat number.

Here's what the `Row` component looks like. Look at the code first, and then let's talk about what's weird here:

chapter_04/02/app/javascript/components/row.tsx

```
1:  import * as React from "react"
 -  import Seat from "./seat"
 -
 -  interface RowProps {
5:    rowNumber: number
 -    seatsPerRow: number
 -  }
 -
 -  const Row = (props: RowProps): React.ReactElement => {
10:   const seatItems = Array.from(Array(props.seatsPerRow).keys()).map(

 -      (seatNumber) => {
```