I've done a refactoring here, splitting the Venue into a VenueHeader and a VenueBody. The header is structurally a different thing, and in React, the general principle is to keep components small and split them up as you add new DOM elements.

We're adding one piece of state to the Venue, which is the number of tickets we're buying at a time. So we need to both manage that state and provide an interface to update it.

We start managing the state right off in the beginning of the component with const [ticketsToBuy, setTicketsToBuy] = React.useState(1). This gives us a property—ticketsToBuy—with an initial value of 1, and a setter function, setTicketsToBuy. The method setTicketsToBuy is a setter function, and we pass it as a prop to the VenueHeader component.

Here's the whole VenueHeader component:

chapter_04/04/app/javascript/components/venue_header.tsx

```
import * as React from "react"

interface VenueHeaderProps {
  seatsPerRow: number
  setTicketsToBuyCount: (n: number) => void
}

const options = (seatsPerRow: number) => {
  const arrayOfNumbers = Array.from(Array(seatsPerRow).keys())
  return arrayOfNumbers.map((i) => (
    <option key={i + 1} value={i + 1}>
      {i + 1}
    </option>
  ))
}

export const VenueHeader = ({
  seatsPerRow,
  setTicketsToBuyCount,
}: VenueHeaderProps): React.ReactElement => {
  const setTicketsOnChange = (event: React.SyntheticEvent): void => {
    const target = event.target as HTMLSelectElement
```