This component does two important things: First, it keeps track of the seat statuses in an array. Second, it defines a click handler to be executed when a seat is clicked. To make that work, the Row component passes that handler function as a prop to the Seat component, namely clickHandler.

The first thing we need to do is call the useState hook again, this time to create an array of seat statuses. The initial value, which is the argument to the useState call, is an array of unsold values, one for each seat in the row.

Using an array or an object as the value of the state in a useState call, rather than an individual value, works differently than you might expect. It is important to keep in mind that the argument to the useState method is only applied to the state value the first time the component is drawn. When the component re-renders, that value is ignored.

An implication of that rule is that you generally don't want the argument to the useState method to be dynamic. In our case, it's just a static array of unsold values since we don't expect the number of seats in the row to change. (Later, in Chapter 8, *Talking to the Server*, we'll see what to do when you do want the state to update on re-render, which we'll use to get the server status of each seat into the system.)

It's also important to keep in mind that in order to trigger a re-render based on changing the state of an array value, you need to create a new array. Just updating an element in the array won't do it.

In our implementation, the Row is going to store in the state value whether each seat is unsold or held, and it's going to calculate separately if the seat is valid. In our admittedly contrived business logic, a seat is valid if you can buy the currently expected number of seats starting at the seat and moving right without hitting the end of the row or another held seat.

We start with one ticket to buy and all the seats valid. If we change the ticketsToBuy to 2, we expect the rightmost seat in each row to be invalid because you can't buy a second seat to the right of the end of the row. If ticketsToBuy becomes 3, we