Building CSS in cssbundling-rails

Our CSS setup is deliberately minimal. We are just using Tailwind to build up a CSS file. We aren't using Sass or PostCSS, which are two popular CSS toolkits that allow for further CSS processing. For more information on what those tools do, see Chapter 7, *Bundling*. For more detailed information in installing Tailwind see the Tailwind documentation[39] and the book *Modern CSS with Tailwind*.[40]

We already walked through our CSS setup in Chapter 1, *Getting Started with Client-Side Rails*, but let's look at it again.

Our main Tailwind loading and CSS file is at app/assets/stylesheets/application.tailwind.css:

chapter_05/01/app/assets/stylesheets/application.tailwind.css

```
@tailwind base;
@tailwind components;
@tailwind utilities;
```

All this does is tell Tailwind to insert its CSS. We've written no other custom CSS.

The Tailwind setup is governed by the Tailwind configuration file that we've seen before, but which currently looks like this:

chapter_05/01/tailwind.config.js

```
module.exports = {
  content: [
    "./app/views/**/*.(html|turbostream).erb",
    "./app/helpers/**/*.rb",
    "./app/javascript/**/*.(js|ts|tsx)",
    "./config/initializers/simple_form_tailwind.rb",
  ],
}
```

Our package.json file contains the following invocation that we name build:css and run in watch mode (this needs to be one line in the actual file):