```
  transform: rotate(-90deg);
}
```

Note for those who are interested: yes, you can also do the transformations with Tailwind utilities, but we're going to stick to plain CSS for the moment. (If you want to do this in Tailwind, the matching Tailwind utilities would be rotate-90 and -rotate-90, but right now I want to show the CSS syntax.)

We've added two new CSS classes: .is-open and .is-closed. Our new classes have only one CSS property: transform. The transform property can be defined as having one or more *transform functions*. In this case, we're using the transform function rotate.

There are lots of transformation functions. The ones you'll use most often are:

- rotate: Rotates the element around its center point by default. The argument to rotate is the amount of turn, clockwise, and can be in degrees (deg), radians (rad), gradients (grad), or just turn.

- scale: Changes the size of the element. If it takes one argument, that scale is used in both the x and y dimension. If there are two arguments, the first is the x scale and the second is the y scale.

- skew: Transforms the element by performing a shear transformation on it. If there is one argument, it's the angle of the shear in the x dimension. If there is a second argument, it's the angle in the y dimension.

- translate: Moves an element. The first argument is the amount to move the element in the x dimension. The optional second argument is the amount to move in the y dimension.

A full list of all the transformation functions can be found online.[41]

So, we've got an is-open class that rotates our image 90 degrees clockwise, leaving it pointing down, and an is-closed class that rotates the image 90 degrees counter-clockwise, leaving it pointing up. Those classes will affect their