That means that properties that have discrete enumerated values, like display, can't be transitioned, and you also usually can't transition to or from magic values like height or width auto.

- The second element is the amount of time you want the transition to take, which is defined either in seconds (s) or milliseconds (ms).

- The third element is a timing function that determines the rate at which the value changes across the transition. The default is linear, meaning the rate is the same for the entire time. Our code uses ease-in-out, which slows the rate of change at the beginning and end of the transition, and speeds it up across the middle. There are other timing functions, should you want to investigate.[42]

- The last element, which our code doesn't have, is a delay—the amount of time to wait before starting the transitions.

What our code is saying is that when any property in our DOM element changes, spread that change out over 0.5 seconds, and use an ease-in and ease-out function to manage the rate of that change.

If we add the new CSS class to the image_tag call that is displaying the image, then just like that, when we click that button, the transition from down to up and back is animated. This effect is a little hard to get across in a screenshot, but trust me on this.

chapter_05/03/app/views/favorites/_list.html.erb

```
<button
  class="<%= SimpleForm.button_class %>"
  data-controller="css-flip"
  data-css-flip-status-value="true"
  data-css-flip-off-class="is-closed"
  data-css-flip-on-class="is-open"
  data-action="click->css#toggle click->css-flip#toggle">
 <%= image_tag(
     "chevron-right.svg",
     width: 25,
```