The only problem with importing via JavaScript is that esbuild is going to want to put its associated JavaScript in the file app/assets/builds/application.css to be parallel to the application.js that esbuild is already creating. If that filename seems familiar, that's because we're already outputting the CSS from Tailwind to that file.

Sadly, the two files won't append to each other; one of them will just continually be overwriting the other. What we need to do then, is to rename the output of the Tailwind CLI process by changing the relevant line in package.json to: "build:css": "tailwindcss -i ./app/assets/stylesheets/application.tailwind.css -o ./app/assets/builds/tailwind.css",

What's changing is the file at the end after the -o switch; that is the name of the output file, and we're changing it to tailwind.css.

We also need to make sure the new CSS file is loaded into the browser. In our app/views/layouts/application.html.erb file, we include the new file in our stylesheet_link_tag call: <%= stylesheet_link_tag "application", "tailwind", "data-turbo-track": "reload" %>

The stylesheet_link_tag helper takes an arbitrary number of file arguments and includes them all.

At this point, we've loaded the Animate.css library. Its JavaScript is bundled with our JavaScript bundle, and its CSS is bundled into the application.css file and passed on to the browser. Our existing Tailwind CSS file now goes to tailwind.css and is also passed to the browser. If you run bin/dev and trigger the build, you'll see all those files in the app/assets/build directory.

Using Animate.css

Now we can animate our transitions by adding the CSS class animate__animated to any element and then following that with one of the several specific animation classes that Animate.css provides, like animate__fadeInUp—Animate.css uses two underscore characters between animate and whatever comes after it. (It's probably worth mentioning that there are a couple of plugins that add Animate.css functionality directly to Tailwind, but we'll be doing it separately here.)

Going back to our Turbo Streams example, when we add something to the