run. In addition to our main Stimulus and React libraries, our code has a lot of dependencies related to Tailwind, and also esbuild itself, and a number of TypeScript type declaration packages (the ones that start with `@types`), and a few other things that don't really fit in any of those previous groups, like `animate.css` or `styled-components`.

Each of the package names is the key of a key/value pair, where the key is the name of the package and the value represents the version of the package you are targeting. The version can be an exact match for the version being used by the code, as in `"stimulus": "3.0.1"`, but often the version number is prefixed with either `>`, which means any version greater than the listed version is okay, or `^`, which means the version being used must match the major and minor version but can have a higher patch version. So `"stimulus": "^3.0.0",` matches version 3.0.0 and also 3.0.5 but not 3.1.0. If you are familiar with Bundler, this is the way the squiggly arrow operator (`~>`) works. If you want to match any version, the version string should be either empty, set within quotes (`" "`), or set as a wildcard character (`"*"`) (you may see wildcards in the sample code because for book purposes it's easier to keep up with version changes that way).

You use Yarn to add items to the dependencies list with the command `yarn add`, as in `yarn add typescript`. Yarn will add the most recent version of the module, saving the actual code to the `node_modules` directory, adding the version information to the `yarn.lock` file and also adding the version to the dependencies list, prefixed by a `^`. If you want, you can specify an exact version, as in `yarn add typescript@3.3.0`. You remove dependencies with `yarn remove`, as in `yarn remove typescript`. Many libraries support `@latest` or `@beta` to retrieve current versions without knowing exactly what number those versions are.

devDependencies

devDependencies are similar to dependencies but they are for tools that are only used in development, not in execution. Our list currently includes a bunch of linting libraries like `eslint` and `prettier`, as well as `tsc-watch`. You use `yarn`