file types:

- Files with a .jsx or .tsx extension are automatically converted using React JSX syntax.
- JSON files can be imported using something like import data from "./sample.json", in which case the JSON file will be parsed and assigned to that variable.
- Similarly, .txt files can be imported and the resulting value is a string.
- As we saw in Chapter 5, *Cascading Style Sheets*, .css files can be imported via JavaScript, in which case they are exported as <entry>.css, where entry is the name of the top level file that imported the CSS. In our earlier case, the entry file was application.js, so the resulting CSS went to application.css. You can also use a CSS file as an entry point, but given the Rails CSS tools, we probably won't need to do that.

Configuring esbuild

You can pass a wide variety of command-line options to esbuild.[58] We've already seen --bundle, --sourcemap, and --outdir, as well as --watch, which we use in our Procfile. Following are additional options that seem most relevant to a Rails application.

–analyze
: You can get a simple report of the contents of your bundle with --analyze, which is just a listing of which input files go into which output file and how much of they file they contain. By making it --analyze=verbose, you also get diagnostics about the import path by which each file is included.

–loader
: The --loader option enables you to specify loading behavior for a given file type. For example, if you wanted to be able to load .md markdown files as raw text, you could use --loader:.md=text (the syntax here being a colon followed by the extension, followed by the name of the loader, which can be base64, binary, dataurl, file, or text, all of which will read in the file and import