These days, Turbo includes this package by default, but if you are having trouble on Safari, you can install it yourself with the following command:

```
$ yarn add form-request-submit-polyfill
```

The method we need is called requestSubmit. (I'll explain why in a moment.)

Now, some logistics. To get client-side search to work, we need a functional server-side search. This isn't a book about server-side search optimization, so we'll go with something simple:

chapter_08/01/app/models/concert.rb

```
def self.search(query)
  joins(:bands)
    .where("concerts.name ILIKE ?", "%#{query}%")
    .or(Concert.where("concerts.genre_tags ILIKE ? ", "%#{query}%"))
    .or(Concert.joins(:bands).where("bands.name ILIKE ?", "%#{query}%"))
    .uniq
end
```

In this code, we're using SQL like statements to return any concert where the concert name, a band's name, or the list of genres contains the query string as a substring. We're throwing a uniq on the end because otherwise we'll get duplicate entries if multiple band names match. This is in no way complex enough to be a full production-level search, but it's fine for now.

We need to create a regular Rails endpoint for this search, and the natural place for it is the index method of the ConcertsController:

chapter_08/01/app/controllers/concerts_controller.rb

```
def index
  @query = params[:query]
  @concerts = Concert.search(@query)
end
```

We also need a view for this. Here's the outer part:

chapter_08/01/app/views/concerts/index.html.erb