```
        max-w-screen-lg w-full
        mr-20 ml-32 px-6 py-2 mt-2
        overflow-y-auto overscroll-contain"
    data-search-target="results"
    data-action="click@window->search#resetOnOutsideClick">
```

The new line here is data-action="click@window->search#resetOnOutsideClick". Stimulus allows you to attach global event listeners by appending your event name with @window to add listeners for the entire window, or @document for listeners on the global document. In this case, a click anywhere in the window will go to the SearchController's resetOnOutsideClick method, so we'd better write that (this functionality is based on similar code from Hey.com):

chapter_08/02/app/javascript/controllers/search_controller.ts

```
resetOnOutsideClick(event: Event): void {
  if (!this.element.contains(event.target as HTMLElement)) {
    this.reset()
  }
}

reset(): void {
  this.resultsTarget.classList.add("hidden")
  this.resultsTarget.innerText = ""
  this.inputTarget.value = ""
}
```

Hey, I Can See Your JavaScript



One of the reasons I'm able to use Hey.com as a great source of how to use Hotwire to build a website is that the Hey team has decided not to hide or obfuscate their run-time JavaScript. If you are running Hey.com, you can see the JavaScript in the browser inspector source tab. Being able to read a site's client code used to be common, but as obfuscation tools became available, most sites decided to hide