the SoldOutDataController:

chapter_08/03/app/views/concerts/_concert.html.erb

```
<article
  class="my-4"
  data-sold-out-data-target="concert"
  data-controller="concert"
  data-concert-id-value="<%= concert.id %>"
  data-concert-sold-out-value="<%= concert.sold_out? ? "true" : "false" %>"
  data-concert-tickets-remaining-value="<%= concert.unsold_ticket_count %>">
```

We have five relevant data attributes in this code block. First, we use data-sold-out-data-target to declare the element a concert target of the SoldOutDataController, then we declare the element to have a data-controller of its own: concert. Then we declare three values for the concert controller: an ID, a true or false for sold out, and a "tickets remaining" value. We populate all of these server side with their correct initial values.

It's probably worth mentioning that as simple as this is, by setting the SoldOutDataController outside of this partial, we're creating a dependency where using this partial expects there to be a SoldOutDataController defined elsewhere in the view. That's fine for our purposes right now—we're only using the view in a case where we have such a controller—but it's something to keep an eye on in your own Stimulus applications.

Later in the same file, we replace the entire HTML tag that had the count of remaining tickets with a blank tag that is a target of the concert controller:

chapter_08/03/app/views/concerts/_concert.html.erb

```
<span data-concert-target="tickets"></span>
```

And now, the big reveal that ties it all together: the ConcertController:

chapter_08/03/app/javascript/controllers/concert_controller.ts

```
import { Controller } from "@hotwired/stimulus"
```