to Row to Seat—and they all change at least a little bit.

We start with a small change to the top-level call in our pack entry point, just changing it so the setup data is being passed in the props.

First we need to change the concert show page to send some data attributes:

chapter_08/04/app/views/concerts/show.html.erb

```
<div id="react-element"
    data-row-count="<%= @concert.venue.rows %>"
    data-seats-per-row="<%= @concert.venue.seats_per_row %>"
    data-concert-id="<%= @concert.id %>"></div>
```

And then in our parent React element, we can grab those data attributes and send them as props to the Venue component:

chapter_08/04/app/javascript/components/venue_display.tsx

```
import * as React from "react"
import { createRoot } from "react-dom/client"
import Venue from "./venue"

document.addEventListener("turbo:load", () => {
  if (document.getElementById("react-element")) {
    const container = document.getElementById("react-element")
    const root = createRoot(container)
    root.render(
      <Venue
        rowCount={parseInt(container.dataset.rowCount, 10)}
        seatsPerRow={parseInt(container.dataset.seatsPerRow, 10)}
        concertId={parseInt(container.dataset.concertId, 10)}
      />
    )
  }
})
```

Now, we need to update the Venue to use that data.

The Venue Component

The Venue component fetches the data from the server so that each individual Seat