specifying a new endpoint, /shopping_carts, and that the call is a POST.

We're also adding two headers. The X-CSRF-Token header is used by Rails to verify that the form actually comes from the application itself and to prevent a cross-site scripting attack. The value csrfToken() is generated by the Rails helper csrf_meta_tags in our application layout; we are just reading it here. Setting the content type to JSON lets us send the body as JSON, which we then do, setting a JSON object with the concertId, the row and seatNumber, the new status, and the number of tickets to buy. The endpoint will update ticket values, and subsequent calls to query for ticket status will show these tickets as held.

Finally, the Seat itself mostly just changes by adding a status color for "purchased". Because we're passing the status to the seat directly, we no longer have to pass the entire TicketData to the Seat.

chapter_08/04/app/javascript/components/seat.tsx

```
import * as React from "react"
import styled from "styled-components"

const stateColor = (status: string): string => {
  if (status === "unsold") {
    return "white"
  } else if (status === "held") {
    return "green"
  } else if (status === "purchased") {
    return "red"
  } else {
    return "yellow"
  }
}

interface SquareProps {
  status: string
  className?: string
}
const buttonClass = "p-4 m-2 border-black border-4 text-lg"

const ButtonSquare = styled.span.attrs({
  className: buttonClass,
```