That's a good thought, because even if we make that change, we still have a problem, which is all the *other* Turbo Stream calls in app/views/favorites/create.turbo_stream.erb (for example, updating the favorite count in the nav bar) happen in the browser that originates the action via the form response, but not in the browser that receives the action via the ActionCable response.

This issue can be fixed in a couple of different ways. One way is to split each of the individual bits of the existing Turbo Stream response into its own partial and create a different callback for each one. However, because we already have a file that has all our Turbo Stream responses together, it seems easier to just adapt that and only have one callback. The most straightforward way to do this is to adapt our existing create and destroy responses to be partial views that expect favorite to be a local variable, like this:

chapter_09/02/app/views/favorites/_create.turbo_stream.erb

```
<%= turbo_stream.append("favorite-concerts-list", favorite) %>
<%= turbo_stream.replace(dom_id(favorite.concert)) do %>
  <%= render(favorite.concert, user: user) %>
<% end %>
<%= turbo_stream.update("no-favorites") do %>
   
<% end %>
<%= turbo_stream.update(
      "favorites-count",
      plain: user.favorites.count
    ) %>
```

chapter_09/02/app/views/favorites/_destroy.turbo_stream.erb

```
<%= turbo_stream.remove(dom_id(favorite)) %>
<%= turbo_stream.replace(dom_id(favorite.concert)) do %>
  <%= render(favorite.concert, user: user) %>
<% end %>
<% if user.favorites.empty? %>
  <%= turbo_stream.update("no-favorites") do %>
    No favorite concerts yet
  <% end %>
<% end %>
<%= turbo_stream.update(
      "favorites-count",
```