general ActionCable implementation, Turbo::StreamsChannel.broadcast_stream_to. The arguments are the name of the channel—still user, :favorites—and the content to be sent, which we're generating by calling ApplicationController.render directly. The first argument is the format, and the remaining arguments describe the rendering.

One other thing: we no longer want the form response to have any content because all the changes will be broadcast via the ActionCable. In the FavoritesController, both respond_to lines need to be changed to format.turbo_stream { head(:ok) }.

And with that, we're working again. The favorites list, the concert display, and the navigation count all update in both browsers. We have the same functionality, but we're broadcasting to an arbitrary number of clients logged in to the same page.

In cases when you want to send a message to the same stream to execute the create, update, and destroy actions, turbo-rails provides the shortest shortcut of all. The method, broadcasts_to takes a symbol as an argument and calls that symbol to determine the name of the stream. So where our existing broadcast_stream_to takes user as an argument, you would use the symbol form broadcasts_to(:user), and turbo-rails calls self.user at run time to determine the stream name.

By using broadcasts_to, you generate three callbacks: an append turbo stream when a record is created, a replace turbo stream when a record is updated, and a remove turbo stream when a record is destroyed. All three have slightly different defaults, but they all use the dom_id of the record where they can.

For example, in our Favorites class, if we wrote broadcasts_to(:user), our destroy action would remove an element with dom_id(self) based on the record being removed, and the update action would similarly expect to update dom_id(self). The create callback is different because you would not expect an element with the dom_id of a new record to exist already. For create, there is a default that an append action is sent targeting an element with an ID of the plural name of the record, which in our case is favorites. Also remember that you can override those defaults. For example, you can change the append action to a prepend action by passing action: