```
% rails generate channel ScheduleChannel
```

This creates a few files:

- A client-side ActionCable channel for our new channel at app/javascript/channels/schedule_channel.js
- A Ruby file for the server-side ActionCable channel at app/channels/schedule_channel.rb
- A test file in spec/channels/schedule_channel_spec.rb (since we have RSpec installed)

If this is your first ActionCable Rails generation, Rails will also create an index.js file for app/javascript/channels. Like the similar file created for Stimulus controllers, this will automatically load any file in that directory ending in _channel.js. Rails will also create a file at app/javascript/channels/consumer.js, which frankly, is just a shortcut for calling the ActionCable method createConsumer. (It will make more sense in a minute when we talk about our client-side code.) We are going to ignore these boilerplate files and integrate ActionCable ourselves. It also adds a line to our app/javascript/application.js importing the channels, which it put at the bottom of the file and which I moved to the top with the other imports.

The first thing we need to do server side is define the channel. The channel does not do very much here:

chapter_09/03/app/channels/schedule_channel.rb

```
class ScheduleChannel < ApplicationCable::Channel
  def subscribed
    stream_from("schedule")
  end

  def unsubscribed
    # Any cleanup needed when channel is unsubscribed
  end
end
```

The two methods, subscribed and unsubscribed, are automatically called by ActionCable when a new connection subscribes to the channel and when that