This is a little more complicated than our earlier channel. In the subscribed method, our stream_from name is now a dynamic string: concert_#{params[:concert_id]}". This suggests two things. First, it means that different concerts will have different streams, so we don't have to worry on the client about seeing messages not meant for the page we are on. It also means that the client will need to pass the concert ID as a parameter when it subscribes.

And you probably noticed the added_to_cart method. This method is called when the client sends a message that tickets are to be added to the cart. It combines the functionality we had put in the ShoppingCartsController to update tickets and the functionality we had in TicketsController to return a data structure of all the tickets sorted by row. I've refactored that functionality into the Shopping Cart and Ticket classes, as shown here:

chapter_09/04/app/models/shopping_cart.rb

```
class ShoppingCart < ApplicationRecord
  belongs_to :user

  def add_tickets(
    concert_id:, row:, seat_number:, tickets_to_buy_count:, status:
  )
    seat_range = seat_number...seat_number + tickets_to_buy_count
    tickets = Ticket.where(
      concert_id: concert_id, row: row, number: seat_range
    ).all
    tickets.update(status: status, user: user)
  end
end
```

chapter_09/04/app/models/ticket.rb

```
def self.for_concert(concert_id)
  return Ticket.all unless concert_id
  Ticket.where(concert_id: concert_id)
    .order(row: :asc, number: :asc)
    .all
    .reject(&:refunded?)
end
```